





HOW PATTERN OBJECT MODEL SAVED MY LIFE

Presented by Gjore Zaharchev







GJORE ZAHARCHEV

- Quality Assurance Coordinator @ Seavus group
- 13 years hands on experience
- Software Testing Trainer
- MeetUp speaker
- Conference Speaker







AGENDA

- Challenges
- Design Patterns
- Improved Pattern Objects
- Similar solutions





User Conference on Advanced Automated Testing





CHALLENGES









You are fired!!

User Conference on Advanced Automated Testing







PEOPLE CHALLENGES

- People don't know programming!
- People don't have time to learn programming!
- People don't have technical skills!
- Clients do not allow less experienced people to work on automation.







TOOLS CHALLENGES

- Human Readable Tests
- Easy Knowledge Transfer
- Troubleshooting Easiness
- Boost Test Reliability
- Accelerate Test Execution
- Extend the Framework to Fit Your Needs









DESIGN PATTERNS







MOST COMMON DESIGN PATTERNS

- Page Object Model
- Page Factory







POM ADVENTAGES

- Code Reuse
- Maintainability
- Readability





PAGE FACTORY

- Improved code
- Shorter code





```
public void page_object_click() {
         driver.findElement(By.xpath("//xpath")).click();
}
```







```
public void page_object() {
    WebElement element;
    element = driver.findElement(By.xpath("//xpath"));
    element.click();
}
```







```
WebElement element;
WebElement element2;
public void page_object() {
    element = driver.findElement(By.xpath("//xpath"));
    element.click();
}
public void page_object2() {
    element2.findElement(By.xpath("//xpath")).click();
}
```







```
public void page_object() {
    WebDriverWait wait = new WebDriverWait(driver, timeOutInSeconds: 20);
    wait.until(ExpectedConditions.visibilityOfElementLocated(By.xpath("//xpath/element"))).click();
}
```







```
public void page_object(){
    WebElement element;
    WebDriverWait wait = new WebDriverWait(driver, timeOutInSeconds: 20);
    element = wait.until(ExpectedConditions.visibilityOfElementLocated(By.xpath("//xpath/element")));
    element.click();
}

public void page_object2(){
    WebElement element;
    WebDriverWait wait = new WebDriverWait(driver, timeOutInSeconds: 20);
    wait.until(ExpectedConditions.visibilityOfElementLocated(By.xpath("//xpath/element")));
    element = driver.findElement(By.xpath("//xpath"));
    element.click();
}
```







```
public void login() {
    WebDriverWait wait = new WebDriverWait(driver, timeOutInSeconds: 20);
    wait.until(ExpectedConditions.visibilityOfElementLocated(By.id("username"))).sendKeys( ...charSequences: "test.user");
    driver.findElement(By.id("password")).sendKeys( ...charSequences: "P@$$wOrd");
}
```







```
WebDriverWait wait = new WebDriverWait(driver, timeOutInSeconds: 20);
public void register() {
    try {
        Thread.sleep( millis: 5000);
    }catch (Exception e) {
        System.out.println(e);
    wait.until(ExpectedConditions.visibilityOfElementLocated(By.id("email"))).
            sendKeys ( ...charSequences: "test.user@gmail.com");
    try {
        Thread.sleep( millis: 2000);
    }catch (Exception e) {
        System.out.println(e);
    driver.findElement(By.id("password")).sendKeys( ...charSequences: "P@$$wOrd");
    try {
        Thread.sleep( millis: 1000);
    }catch (Exception e) {
        System.out.println(e);
```









IMPROVED PATTERN OBJECT























ELEMENTS AND ACTIONS

- Driver/Browsers Initialize
- Buttons & Links Click
- Input Fields Type Text
- Alerts Do something with alerts
- Dropdowns/Combobox Select
- Texts Retrieve Text/Attribute Value









- Alerts
- Button
- Oropdown
- C Files
- Gestures
- C Input
- © Key
- Misc
- 📇 package-info.java



- Database
- DataSources
- Extract
- Navigate
- Validate
- Wait







```
/**...*/
public WebElement getElement(final By by) {
    try {
        return vaitElement.until(ExpectedConditions.visibilityOfElementLocated(by));
    } catch (NoSuchElementException e) {
        e.printStackTrace();
        return null;
/**...*/
public List<WebElement> getAllElements(final By by) {
    try {
        return vaitElement.until(ExpectedConditions.visibilityOfAllElementsLocatedBy((by)));
    } catch (NoSuchElementException e) {
        e.printStackTrace();
        return null:
```







```
/** Click on particular button or link. ...*/
public void click(final By by) {
    try {
        getElement(by).click();
    } catch (Exception e) {
/** Click on particular button or link. ...*/
public void click (final By by, final int index) {
    try {
        getAllElements(by).get(index).click();
    } catch (NoSuchElementException e) {
        e.printStackTrace();
```







```
import com.taw.common.globals.ElementActions;
import org.openga.selenium.By;
public class LoginPage extends ElementActions {
    By username = By.id("username");
    By password = By.id("password");
    By login = By.id("login");
   public void type username(String user) {
        input.type (username, user);
    public void type password(String pass) {
        input.type(password, pass);
    public void login button() {
        button.click(login);
```





User Conference on Advanced Automated Testing





SIMILAR SOLUTIONS

